

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020104 A1

(51) International Patent Classification⁷: **B02C 19/00**

(21) International Application Number:
PCT/SE2003/001321

(22) International Filing Date: 27 August 2003 (27.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0202536-9 28 August 2002 (28.08.2002) SE

(71) Applicant (for all designated States except US): SAND-
VIK AB [SE/SE]; S-811 81 Sandviken (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): DALLIMORE,
Rowan [GB/GB]; 5 Charlton Park, Midsomer Norton,
Radstock BA3 4BN (GB). FENSOME, George [GB/GB];
11 Speedwell Close, Thornbury, Bristol BS35 1UD (GB).

(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö
(SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ (utility model), CZ, DE (utility model), DE, DK (utility
model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI
(utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT,
LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO,
NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK,
SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A ROTOR FOR A CRUSHER



(57) Abstract: A rotor for a vertical shaft impact crusher comprises a vertical wall segment (20) having a first wall portion (20a), which is tangential to the rotor (1) and is located adjacent to the periphery of the rotor (1), and a second wall portion (20b), which is angled in relation to said first wall portion (20a) and extends from the first wall portion (20a) into the rotor (1). The second wall portion (20b) comprises a first section (80), which extends from the interior of the rotor (1) towards its periphery and forms an obtuse first angle (S) with said first wall portion (20a), and a second section (84), which connects the first section (80) and the first wall portion (20a). The second section (84) and said first wall portion (20a) form a second angle (T), which is smaller than said first angle (S), and at least one pocket (88) for retaining material.